



Unistrut® Channel P3300(T) 41x21x2,5mm / on length	Unistrut® Channel P1000(T) 41x41x2,5mm / on length																																																								
Part number build-up	Part number build-up: <b>2031-X-XX-XXXX</b>																																																								
-X: 1=galvanised / 2= SS / 3= HDG	-X: 1=galvanised / 2= SS / 3= HDG																																																								
-XX: 00=slotted / 01= slotless	-XX: 00=slotted / 01= slotless																																																								
-XXXX: length channel in mm (example: -0500=500mm)	-XXXX: length channel in mm (example: -0500=500mm)																																																								
 <p>Technical details:</p> <table border="1"> <tr><td>Wall thickness</td><td>t</td><td>(mm)</td><td>2.5</td></tr> <tr><td>Area of section</td><td>A</td><td>(cm<sup>2</sup>)</td><td>1.97</td></tr> <tr><td>Weight</td><td></td><td>(Kg/m)</td><td>1.76</td></tr> <tr><td>Standard length</td><td></td><td>(m)</td><td>3 &amp; 6</td></tr> <tr><td>Outer dimensions</td><td>HxW</td><td>(mm)</td><td>21x41</td></tr> <tr><td>Slot size</td><td>LxW</td><td>(mm)</td><td>25x11</td></tr> <tr><td>Slot pitch</td><td></td><td>(mm)</td><td>50</td></tr> </table>	Wall thickness	t	(mm)	2.5	Area of section	A	(cm <sup>2</sup> )	1.97	Weight		(Kg/m)	1.76	Standard length		(m)	3 & 6	Outer dimensions	HxW	(mm)	21x41	Slot size	LxW	(mm)	25x11	Slot pitch		(mm)	50	 <p>Technical details:</p> <table border="1"> <tr><td>Wall thickness</td><td>t</td><td>(mm)</td><td>2.5</td></tr> <tr><td>Area of section</td><td>A</td><td>(cm<sup>2</sup>)</td><td>3.00</td></tr> <tr><td>Weight</td><td></td><td>(Kg/m)</td><td>2.73</td></tr> <tr><td>Standard length</td><td></td><td>(m)</td><td>3 &amp; 6</td></tr> <tr><td>Outer dimensions</td><td>HxW</td><td>(mm)</td><td>41x41</td></tr> <tr><td>Slot size</td><td>LxW</td><td>(mm)</td><td>28x14</td></tr> <tr><td>Slot pitch</td><td></td><td>(mm)</td><td>50</td></tr> </table>	Wall thickness	t	(mm)	2.5	Area of section	A	(cm <sup>2</sup> )	3.00	Weight		(Kg/m)	2.73	Standard length		(m)	3 & 6	Outer dimensions	HxW	(mm)	41x41	Slot size	LxW	(mm)	28x14	Slot pitch		(mm)	50
Wall thickness	t	(mm)	2.5																																																						
Area of section	A	(cm <sup>2</sup> )	1.97																																																						
Weight		(Kg/m)	1.76																																																						
Standard length		(m)	3 & 6																																																						
Outer dimensions	HxW	(mm)	21x41																																																						
Slot size	LxW	(mm)	25x11																																																						
Slot pitch		(mm)	50																																																						
Wall thickness	t	(mm)	2.5																																																						
Area of section	A	(cm <sup>2</sup> )	3.00																																																						
Weight		(Kg/m)	2.73																																																						
Standard length		(m)	3 & 6																																																						
Outer dimensions	HxW	(mm)	41x41																																																						
Slot size	LxW	(mm)	28x14																																																						
Slot pitch		(mm)	50																																																						
Complete Unistrut overview: see <a href="http://www.fox-clamps.com">www.fox-clamps.com</a>	Complete Unistrut overview: see <a href="http://www.fox-clamps.com">www.fox-clamps.com</a>																																																								

### Unistrut® Mountingracks



**The set consists off:**

- 1) Channel, Unistrut P1000T (slotted) on length. Choose width and height of rack (see below)
  - 2) QB41 Baseplate (Kwikstrut)
  - 3) Uni lock locknut (Kwikstrut)
  - 4) QFA Angle fitting, 90° (Kwikstrut)
  - 5) \*Drill Anchor for mounting baseplates.
  - 6) Cableclamp set: choose your model , see datasheet
  - 7) Cable block set: choose your model, see datasheet
- \* Drill anchorset consists off: drill anchors, hexagon bolts, washers

#### Unistrut Mountingracks art. numbers

Artikel nummer opbouw: <b>2024-X-XX-XXX-X</b>
-X: 1= galvanised / 2= SS / 3= HDG
-XX: Choose height of rack. example. -05=500 mm / -15=1500 mm
-XXX: Choose width rack (horizontal.) example. -050= 500 mm / -150= 1500 mm
-X: Choose amount of horizontals the example of picture is 2x

Example: Rack galvanised, height= 1000 mm, Width: 1500 mm, 3 layers; will be part nr. 2024-1-10-150-3